Christie Access Series LCD panels

The perfect balance between performance and price

Technical sp	ecifications	Christie UHD551-L	Christie UHD651-L
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm
	native resolution	• UHD 3840 x 2160 (16:9)	
	backlight	• Edge-lit LED	
	LED lifespan	• 50,000 hours to 50% brightness	
	display orientation	• Landscape	
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm
	nominal bezel size (bottom/side/top)	• 14mm/11mm/11mm	• 21mm/15mm/15mm
	brightness	• 400 nits (cd/m²) typical	
	contrast ratio (full field)	• 1200:1 typical	• 4000:1 typical
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 60Hz	
	response time	• 8 ms typical	
	color space (CIE 1931)	• 68% typical	• 75% typical
	display colors	• 10 bit, 1.07 billion colors	• 8 bit, 16.7 million colors
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • 2 x USB 2.0 • USB 3.0	
	outputs	DisplayPort 1.2a; HDMI 2.0	
Audio	inputs	• RCA (L/R) line in	
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender	
Power	input rating	• 100-240 VAC @ 50-60Hz	
	power consumption	70W typical without OPS	• 73W typical without OPS
		• 140 W maximum without OPS	• 140W maximum without OPS
		• <=0.5W in standby without OPS	• <=0.5W in standby without OPS
Environment	operating temperature	• 32-104°F (0-40°C)	
	storage temperature	• -4-140°F (-20-60°C)	
	operating humidity	• 20-90% RH non-condensing	(14/11/2) 57.4.22.4.2011/4450.044.24
Physical	size (panel only)	• (WxHxD) 48.7 x 28 x 4.1" (1238 x 712 x 104mm)	• (WxHxD) 57.4 x 33.1 x 3.8" (1459 x 841 x 96mm)
	weight	• 38.6lbs (17.5kg)	• 49.6lbs (22.5kg)
	mounting	• VESA 400 x 200mm, M6	• VESA 400 x 400mm, M6
Runtime		Designed for 16/7 operation featuring a reliable power supply ¹	
Features		Commercial grade LCD with LED backlight OPS slot Anti-glare treatment 2 x 8W speakers On/off scheduler USB playback of Photo/Video/MP3 HDMI-CEC Source switching for failover Kensington lock Wi-Fi® Bluetooth Miracast device connectivity Pixel shifting	
Accessories		• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA551 up to 10 point IR touch overlay (for 55") and TA651 up to 10 point IR touch overlay (for 65")	
Warranty		Three year parts and labor limited warranty Contact an authorized Christie representative for full details	

¹ Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com

Corporate offices Worldwide offices

Christie Digital Systems USA, Inc. ph: 714 236 8610

Christie Digital Systems Canada Inc. ph: +55 (11) 2548 4753 ph: 519 744 8005

Australia ph: +61 (0) 7 3624 4888 China (Beijing) ph: +86 10 6561 0240 China (Shanghai) ph: +86 21 6278 7708

ph: +33 (0) 1 41 21 44 04

ph: +49 2161 664540

ph: +91 (080) 6708 9999 Japan (Tokyo) ph: 81 3 3599 7481 Korea (Seoul) ph: +82 2 702 1601

ph: +52 55-4744-1790

Republic of South Africa ph: +27 11 251 0000

Russian Federation and Eastern Europe ph: +36 (0) 1 47 48 100

ph: +65 6877 8737 ph: +34 91 633 9990 United Arab Emirates ph: +971 4 3206688

United Kingdom ph: +44 (0) 118 977 8000 United States (Arizona)

ph: 602 943 5700 United States (New York) ph: 646 779 2014

Independent sales consultant offices

ph: +39 (0) 2 9902 1161









